

DECLARATION OF PERFORMANCE

No.....25201202670.....

1. Unique identification code of the product-type:

DKMU24/DKSM24/PAEF11M/AMCH24/DKMU1224/DKTW24

2. Type, batch or serial number or any other element allowing identification of the construction products as required pursuant to Article 11(4):

Glazed Porcelain Tile and Mosaics (Batch or Serial Number see label and products)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Dry-Pressed ceramic tiles for floorings and wall finishes, internal and external in accordance with EN14411:26

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

MAX NOVACASA

Room 1908-1912, 19/F, Everbright International Trade Center, Jida, Zhuhai, China

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

NOT RELEVANT

6. System or systems of assessment and verification of constancy of performance of the construction products as set out in Annex V:

SYSTEM 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

NOT RELEVANT

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Issued the Certificate of Conformity Test Number 25201202670 regarding a statement on the product performance subject to the standard EN14411:2006

9. Declaration performance

Essential characteristics (see Note 1)	Performance (see Note 2)	Harmonised technical specification (see Note 3)
Reaction to fire	Class A1fl (Decision 96/603/EEC as amended)	EN14411:2006
Breaking strength	≥1300N (EN ISO 10545-4)	EN14411:2006
Modulus of rupture	≥35N/mm ² (EN ISO10545-4)	EN14411:2006
Thermal shock resistance	Passed (EN ISO 10545-9)	EN14411:2006
Durability: Freeze / thaw cycle	Passed (EN ISO10545-12)	EN14411:2006
Skid resistance	NPD	EN14411:2006
Slipperiness	Dry: > 35, Wet: < 25 (BS 7976-2:2002)	EN14411:2006
Release of dangerous substances	NPD	EN14411:2006

Where pursuant to Articles 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

.....NOT RELEVANT

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.


This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Margery.sun Sales Admin manager

.....
(name and function)

.....Zhuhai Jun. 24, 2013.....
(placed and date of issue)



.....
(signature)